



Product Service

CERTIFICATE

No. Z2 099333 0111 Rev. 03

Holder of Certificate: **LONGi Green Energy Technology Co., Ltd.**

No. 388, Middle Hangtian Road
Chang'an District
710100 Xi'an City, Shaanxi
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product:

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Mono-crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062401243-03

Valid until: 2029-10-27

Date, 2024-10-28

(Zhulin Zhang)

CERTIFICATE

No. Z2 099333 0111 Rev. 03

Model(s):

LR5-72HTH-xxxM (xxx=540-600, in step of 5, 144 cells)
 LR5-66HTH-xxxM (xxx=490-550, in step of 5, 132 cells)
 LR5-54HTH-xxxM (xxx=405-450, in step of 5, 108 cells)
 LR5-54HTB-xxxM (xxx=405-445, in step of 5, 108 cells)
 LR5-72HTHF-xxxM (xxx=540-600, in step of 5, 144 cells)
 LR5-72HPH-xxxM (xxx=525-575, in step of 5, 144 cells)
 LR5-66HPH-xxxM (xxx=480-530, in step of 5, 132 cells)
 LR5-60HPH-xxxM (xxx=435-480, in step of 5, 120 cells)
 LR5-54HPH-xxxM (xxx=400-435, in step of 5, 108 cells)
 LR5-72HIH-xxxM (xxx=525-575, in step of 5, 144 cells)
 LR5-66HIH-xxxM (xxx=480-530, in step of 5, 132 cells)
 LR5-60HIH-xxxM (xxx=435-480, in step of 5, 120 cells)
 LR5-54HIH-xxxM (xxx=400-435, in step of 5, 108 cells)
 LR7-72HTH-xxxM (xxx=590-635, in step of 5, 144 cells)
 LR7-54HTH-xxxM (xxx=445-475, in step of 5, 108 cells)
 LR5-36HTH-xxxM (xxx=260-290, in step of 5, 72 cells)
 LR7-60HTH-xxxM (xxx=495-525, in step of 5, 120 cells)
 LR7-66HTH-xxxM (xxx=550-580, in step of 5, 132 cells)
 LR5-54HTHB-xxxM (xxx=400-420, in step of 5, 108 cells)
 LR7-54HTHF-xxxM (xxx=445-475 in step of 5, 108 cells)
 LR7-72HTHF-xxxM (xxx=590-635 in step of 5, 144 cells)
 LR7-60HTHF-xxxM (xxx=495-525 in step of 5, 120 cells)
 LR7-66HTHF-xxxM (xxx=550-580 in step of 5, 132 cells)
 LR7-72HTB-xxxM, (xxx=595-650 in step of 5)
 LR7-66HTB-xxxM, (xxx=545-595 in step of 5)
 LR7-60HTB-xxxM, (xxx=495-545 in step of 5)
 LR7-54HTB-xxxM, (xxx=450-485 in step of 5)
 LR7-72HVHF-xxxM, (xxx=620-665 in step of 5)
 LR7-72HVH-xxxM, (xxx=620-665 in step of 5)
 LR7-54HVHF-xxxM, (xxx=460-500 in step of 5)
 LR7-54HVH-xxxM, (xxx=460-500 in step of 5)
 xxx stands for rated output power at STC.

Parameters:

Fire Safety Class:	Class C according to UL790.
Safety Class:	Class II
Max. System Voltage:	1500V DC
Test Laboratory:	China Telecommunication Technology Labs. CuiHu Cloud Center, No.1 Gaolizhang Road, Wenquan Town Haidian District, Beijing, China.
Construction:	Framed, with Junction box, cable and connector.

Tested according to:

IEC 61215-1:2021
 IEC 61215-1-1:2021
 IEC 61215-2:2021
 IEC 61730-1:2023
 IEC 61730-2:2023
 EN IEC 61215-1-1:2021
 EN IEC 61215-1:2021
 EN IEC 61215-2:2021
 EN IEC 61730-1:2018
 EN IEC 61730-2:2018