


SigenMicro

solution and configuration introduction

SE&MKT 2025/07/04



SigenMicro Balcony Solar



Boundary condition

1. Balcony Solar
2. up to **2 panels**, total power capacity $\leq 800W$
3. Plug & Play connection with Euro Plug


Each system supports :

SigenMicro $\times 1$

Max AC output power **800 W_{ac}***

SigenMicro Balcony Solar

Scenario




Installation

- 1 Selecting a Location
- 2 Measuring the Distance
- 3 Mount the solar panel support beams
- 4 Install the solar panel on the balcony railing
- 5 Repeat the steps above to install another solar panel
- 6 Connect the solar panel and the microinverter



SigenMicro

On-grid _Sigle Phase Micro Inverter Only System



Boundary condition

1. On grid scenario, **multi-string** can be installed according to the site condition
2. up to **50* microinverter** per system
(up to **14 x 1_in_1 microinverter** per string;
up to **7 x 2_in_1 microinverter** per string)
3. Junction box are supplied by installer.
4. Wifi mesh communication, optional AP for wifi extender


Each system supports :

up to SigenMicro × **50 ***

Max AC output power **50 kWac**

* This limitation is refering to the system capacity. For string level limit, please refer to the boundary condition for single string installtion.

On-grid _Sigle Phase Micro Inverter Only System



Boundary condition

1. On grid scenario, **multi-string** can be installed according to the site condition
2. up to **50* microinverter** per system
(up to **14 * 1_in_1 microinverter** per string;
up to **7 * 2_in_1 microinverter** per string)
3. Junction box for **multi-string** installation are supplied by installer.
4. optional AP for wifi extender, optional AP for wifi extender
5. **No communication** between SigenStor and microinverter

Each system supports:

Up to SiggenMicro x 50* ;

Up to SigenStor × 20 ;

Max AC output power **50** kWac (from Microinverter)


Max AC output power **240** kWac (from SigenStor)

Max. ESS capacity **1080** kWh

* This limitation is referring to the system capacity. For string level limit, please refer to the boundary condition for single string installation.

SigenMicro

Backup_Single Phase Micro Inverter + SigenStor



Boundary condition

1. Unstable grid, **whole backup scenario**, **multi-string** installation
2. up to **36* microinverter** per system (up to **14 * 1_in_1** microinverter per string; up to **7 * 2_in_1** microinverter per string)
3. Junction box for **multi-string** installation are supplied by installer.
4. Wifi mesh communication optional AP for wifi extender
5. **No communication** between SigenStor and microinverter

Each system supports :

Up to SigenMicro × **36** (400W) *;

Up to SigenStor × **2**;

Max AC output power **14.5** kWac (from Microinverter)


Max AC output power **18** kWac (from SigenStor)

Max. ESS capacity **108** kWh

* This limitation is referring to the system capacity. For string level limit, please refer to the boundary condition for single string installation.

SigenMicro

On-grid _Three Phase Micro Inverter Only



Boundary condition

1. On grid scenario, **Three phase** installation
2. up to **50*microinverter** per system
(up to **14 * 1_in_1 Microinverter/string**;
up to **7 * 2_in_1 Microinverter/string**)
3. AC combiner boxes (three phase) are supplied by installer.
4. Wifi mesh communication, optional AP for wifi extender


Each system supports :

up to SigenMicro × **50***

Max AC output power **50 kWac**

* This limitation is referring to the system capacity. For string level limit, please refer to the boundary condition for single string installation.

On-grid _Three Phase Micro Inverter Only System



Boundary condition

1. On grid scenario, **multi-string** can be installed according to the site condition
2. up to **50* microinverter** per system
(up to **14 * 1_in_1 microinverter** per string;
up to **7 * 2_in_1 microinverter** per string)
3. Junction box for **multi-string** installation are supplied by installer.
4. optional AP for wifi extender, optional AP for wifi extender
5. **No communication** between SigenStor and microinverter

Each system supports:

Up to SiggenMicro x 50* ;

Up to SigenStor × 20 ;


Max AC output power **50** kWac (from Microinverter)

Max AC output power **600** kWac (from SigenStor)

Max. ESS capacity **1080** kWh

* This limitation is referring to the system capacity. For string level limit, please refer to the boundary condition for single string installation.

Backup_Three Phase Micro Inverter + SigenStor



Boundary condition

1. Unstable grid, **whole backup scenario**, **multi-string** installation
2. up to **50* microinverter** per system
(up to **14 * 1_in_1 microinverter** per string;
up to **7 * 2_in_1 microinverter** per string)
3. Junction box for **multi-string** installation are supplied by installer.
4. Wifi mesh communication optional AP for wifi extender
5. **No communication** between SigenStor and microinverter

Each system supports :

Up to SigenMicro × 50* ;

Up to SigenStor × 20 ;

Max AC output power **50** kWac (from Microinverter)


Max AC output power **600** kWac (from SigenStor)

Max. ESS capacity **1080** kWh

* This limitation is referring to the system capacity. For string level limit, please refer to the boundary condition for single string installation.

SigenMicro

1_in_1 vertical installation



Characteristic ☒


- 1 string.
- 1_in_1 microinverter** system.
- PV panels are installed vertically and next to each other.

Equipment	Quantity	Comment
A1. AC BUS cable	1	1.1m connectors interval
B. Microinverter	1~14	1~9(400, 2.5 mm ²) 1~7(500, 2.5 mm ²) 1~14(400, 4.0 mm ²) 1~11(500, 4.0 mm ²)
C. AC Connector	1~14	1. Equal to the No. of microinverter ; 2. In series with 1.1 m interval AC BUS Cable.
D. AC BUS End Cap	1	Same as the No. of BUS cable string



SigenMicro

2_in_1 vertical installation



Characteristic ☒


1. **One** string.
2. **2_in_1 microinverter** system.
3. PV panels are installed vertically and next to each other.

Equipment	Quantity	Comment
A2. AC BUS cable	1	2.3m connectors interval
B. Microinverter	1~7	1~4(800, 2.5 mm ²) 1~3(1000, 2.5 mm ²) 1~7(800, 4.0 mm ²) 1~5(1000, 4.0 mm ²)
C. AC Connector	1~7	1. Equal to the No. of microinverter ; 2. In series with 2.3 m interval AC BUS Cable.
D. AC BUS End Cap	1	Same as the No. of BUS cable string
E1. DC Extension Cable (1m)	2~14	equal to 2n (n= No. of microinverter)



SigenMicro

1_in_1 horizontal installation



Characteristic☒


1. **1** string.
2. **1_in_1 microinverter** system.
3. PV panels are installed horizontally and next to each other.

Equipment	Quantity	Comment
A2. AC BUS cable	1	2.3m connectors interval
B. Microinverter	1~14	1~9(400, 2.5 mm ²); 1~14(400, 4.0 mm ²) 1~7(500, 2.5 mm ²); 1~11(500, 4.0 mm ²)
C. AC Connector	1~14	1. Equal to the No. of microinverter ; 2. In series with 2.3 m interval AC BUS Cable.
D. AC BUS End Cap	1	Same as the No. of BUS cable string



SigenMicro

2_in_1 horizontal installation



Characteristic ☒

1. **1** string.
2. **2_in_1 microinverter** system.
3. PV panels are installed horizontally and next to each other.

Equipment	Quantity	Comment
A2. AC BUS cable	1	2.3m connectors interval
B. Microinverter	1~6	1~4(800, 2.5 mm ²); 1~6(800, 4.0 mm ²) 1~3(1000, 2.5 mm ²); 1~5(1000, 4.0 mm ²)
C. AC Connector	1~11	1. Equal to 2n-1 (n = the No. of microinverter) 2. In series with 2.3 m interval AC BUS Cable.
D. AC BUS End Cap	1	Same as the No. of BUS cable string
E2. DC Extension Cable (2m)	2~12	Equal to 2n (n= No. of microinverter)
F. Branch Cap	0~7	Equal to n-1 (n= No. of microinverter)
G. MC4 Terminals	1	1 pair of male and female



NEW

SigenMicro AC Cable Kit

SigenMicro AC Cable Kit-40-110-2.5

2.5mm² AC bus cable x 1

End cap x **8**

Branch cap x **10**

Trunk unlock tool x 1

Branch unlock tool x 1

SigenMicro AC Cable Kit-20-230-2.5

2.5mm² AC bus cable x 1

End cap x **4**

Branch cap x **5**

Trunk unlock tool x 1

Branch unlock tool x 1

SigenMicro AC Cable Kit-40-110-4.0

4.0mm² AC bus cable x 1

End cap x **8**

Branch cap x **10**

Trunk unlock tool x 1

Branch unlock tool x 1

SigenMicro AC Cable Kit-20-230-4.0

4.0mm² AC bus cable x 1

End cap x **4**

Branch cap x **5**

Trunk unlock tool x 1

Branch unlock tool x 1



NEW

SigenMicro AC Cable Kit US

SigenMicro US AC Cable Kit-40-3.6ft-12

3.6ft interval
40 connectors
12AWG AC bus cable x 1

End cap x 8

Branch cap x 10

Trunk unlock tool x 1

Branch unlock tool x 1

SigenMicro US AC Cable Kit-20-7.5ft-12

7.5ft interval
20 connectors
12AWG AC bus cable x 1

End cap x 4

Branch cap x 5

Trunk unlock tool x 1

Branch unlock tool x 1

SigenMicro US AC Cable Kit-40-3.6ft-10

1.1m interval
40 connectors
10AWG AC bus cable x 1

End cap x 8

Branch cap x 10

Trunk unlock tool x 1

Branch unlock tool x 1

SigenMicro US AC Cable Kit-20-7.5ft-10

7.5ft interval
20 connectors
10AWG AC bus cable x 1

End cap x 4

Branch cap x 5

Trunk unlock tool x 1

Branch unlock tool x 1



NEW

SigenMicro Plug & DC Cable

SigenMicro Plug Cable-500-1.5



SigenMicro DC Cable-100/3.28ft



SigenMicro DC Cable-200/6.56ft



Thank you.

Enjoy Green Energy



© 2024 Sigenenergy Technology Co., Ltd. All Rights Reserved

Disclaimer: The information on this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.