

## Safety Data Sheets (SDSs)

Product Name: Rechargeable Li-ion Battery System

Commissioner: Ginlong Energy Storage Co., Ltd.

**CVC Testing Technology Co., Ltd.**

# Safety Data Sheets (SDSs)

Ref. No.: RZUN012026-1255-DS3

Page 2 of 9 Pages

Name of Product	Rechargeable Li-ion Battery System
Type/Model	IntelliHome-5kWh-OD 51.2V 100Ah 5kWh
Commissioned by	Ginlong Energy Storage Co., Ltd.
Commissioner address	No.57 Jintong Road, Binhai Industrial Park, DongChen, Xiangshan, 315712 Ningbo, Zhejiang, PEOPLE'S REPUBLIC OF CHINA
Supplier	Ginlong Energy Storage Co., Ltd.
Supplier address	No.57 Jintong Road, Binhai Industrial Park, DongChen, Xiangshan, 315712 Ningbo, Zhejiang, PEOPLE'S REPUBLIC OF CHINA
Inspection according to	GLOBALY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS, Rev.11)
Emergency telephone number	15888076344
Remarks	-
Seal of CVC	
Date of issue: 2026-04-30	

Approved by: Zhang Siyao

*Zhang siyao*

Reviewed by: Liu Zhen

*liuzhen*

Tested by:

Lin Qingyuan

*Lin Qingyuan*

# Safety Data Sheets (SDSs)

Ref. No.: RZUN012026-1255-DS3

Page 3 of 9 Pages

## SECTION 1: Product and company identification

### Product Identifier:

Product name: Rechargeable Li-ion Battery System

Model: IntelliHome-5kWh-OD

### Other means of identification:

Synonyms: None

### Relevant identified use of Product and uses advised against:

Recommended Use: -

Uses advised against: -

### Details of the Supplier of the safety data sheet:

Name: Ginlong Energy Storage Co., Ltd.

Address: No.57 Jintong Road, Binhai Industrial Park, DongChen, Xiangshan, 315712 Ningbo, Zhejiang, PEOPLE'S REPUBLIC OF CHINA

Telephone: 15888076344

Fax: -

Postcode: -

E-mail address: Ruyi.pan@ginlong.com

### Emergency telephone number:

Company Emergency Phone Number: 15888076344

## SECTION 2: Hazard identification

### Classification:

The watt-hour rate of the product is 5kWh, it is belong to the class 9 dangerous goods.

The product is tested according to Section 38.3 of the Manual of Tests and Criteria, the test report number is: RZUN012026-1255

### Other information

Caution! To avoid short circuit, do not place in high temperature environment, put into water, or damage the shell.

## SECTION 3: Composition/information on ingredients

### Chemical characterization: Mixtures

Description: Chemical power supply based on nonaqueous electrolyte. Composed by positive electrode, negative electrode, diaphragm, electrolyte and shell.

Hazardous ingredients:

Common Chemical Name	Chemical Formula	Concentration (%)	CAS No.	EC No.
Lithium Iron Phosphate	LiFePO <sub>4</sub>	49	15365-14-7	604-917-2

# Safety Data Sheets (SDSs)

Ref. No.: RZUN012026-1255-DS3

Page 4 of 9 Pages

Lithium hexafluorophosphate(1-)	LiPF <sub>6</sub>	3	21324-40-3	244-334-7
Graphite	C	24	7782-42-5	231-955-3
Aluminum	Al	6	7429-90-5	231-072-3
Copper	Cu	13	7440-50-8	231-159-6
Polypropylene	(C <sub>3</sub> H <sub>6</sub> ) <sub>n</sub>	5	9003-07-0	618-352-4

Note: N/A=Not apply.

## SECTION 4: First-aid measures

### **First aid measures:**

Eye Contact: Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact: Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation: Move to fresh air. If symptoms persist, call a physician.

Ingestion: Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Swallowing: Do not induce vomiting. Get medical attention.

### **Most Important Symptoms/Effects:**

No information available.

### **Indication of any immediate medical attention and special treatment needed:**

Inform physician. Treat symptomatically.

## SECTION 5: Fire-fighting measures

### **Suitable Extinguishing Media:**

CO<sub>2</sub>, dry chemical powder, wet sand, plenty of water (for cooling).

Unsuitable Extinguishing Media: No information available.

### **Protective Equipment and Precautions for Firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

### **Special hazards arising from the substance or mixture:**

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium batteries contain flammable ingredients that may vent, ignite and produce sparks when subjected to high temperature (>150°C), When damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

# Safety Data Sheets (SDSs)

Ref. No.: RZUN012026-1255-DS3

Page 5 of 9 Pages

## SECTION 6: Accidental release measures

### **Personal precautions, protective equipment and emergency procedures:**

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

### **Environmental precautions:**

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

### **Methods and material for containment and cleaning up:**

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non-combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## SECTION 7: Handling and storage

### **Precautions for safe handling:**

Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse.

More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, rubber gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. No smoking at working site. Materials to Avoid: Strong oxidizing agents, Corrosives.

### **Conditions for safe storage, including any incompatibilities:**

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short-circuits. Materials to Avoid: Strong oxidizing agents, Corrosives.

## SECTION 8: Exposure controls/personal protection

### **Engineering Controls:**

Use ventilation equipment if available. Safety shower and eye bath.

### **Personal Protective Equipment:**

Respiratory System: Not necessary under conditions of normal use.

Eyes: Not necessary under conditions of normal use.

Clothing: Wear appropriate protective clothing.

# Safety Data Sheets (SDSs)

Ref. No.: RZUN012026-1255-DS3

Page 6 of 9 Pages

Hand: Safety gloves.

## **Other Protect:**

No smoking, drinking and eating at working site. Wash thoroughly after handling.  
Should damage occur to the product, PPE of gloves and goggles should be worn.

## **SECTION 9: Physical and chemical properties**

Physical State	Form: Prismatic
	Color: White
	Odour: Odourless
	Odor Threshold: No information available
Change in condition:	
pH, with indication of the concentration	Not determined.
Melting point/freezing point	Not determined.
Initial boiling point and Boiling range:	Not determined.
Flash Point	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Auto-ignition temperature	Product is not self-igniting.
Decomposition temperature	Not determined.
Other Information	No further relevant information available.

## **SECTION 10: Stability and reactivity**

**Reactivity:** Stable under recommended storage and handling conditions (see section 7).

**Chemical stability:** Stable under normal conditions of use, storage and transport.

**Thermal decomposition/conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of Hazardous Reactions:** None under normal processing.

**Hazardous Polymerization:** Hazardous polymerization does not occur.

**Conditions to avoid:** Strong heating, fire, Incompatible materials.

**Incompatible materials:** Strong oxidizing agents. Strong acids.

**Hazardous Decomposition Products:** Carbon oxides, other irritating and toxic gases.

## **SECTION 11: Toxicological information**

# Safety Data Sheets (SDSs)

Ref. No.: RZUN012026-1255-DS3

Page 7 of 9 Pages

**Acute toxicity:** No data available.

**Skin corrosion/irritation:** No irritant effect.

**Serious eye damage/irritation:** Cause serious eye irritation.

**Respiratory or skin sensitization:** No sensitizing effects known.

**Specific target organ system toxicity:** No information available.

*Note: The internal battery materials may cause irritation to eyes and skin.*

## SECTION 12: Ecological information

**Toxicity:** No further relevant information available.

**Persistence and degradability:** No further relevant information available.

**Bioaccumulative potential:** No further relevant information available.

**Mobility in soil:** No further relevant information available.

**Results of PBT and vPvB assessment:**

PBT: Not applicable.

vPvB: Not applicable.

**Other adverse effects:** No information available.

## SECTION 13: Disposal considerations

**Waste treatment methods:**

Recommendation: Lithium batteries are best disposed of as a non-hazardous waste when fully or mostly discharged. Contact a licensed professional waste disposal service to dispose of large quantities materials.

**Other disposal recommendations:**

Disposal should be arranged via specialist recycling

## SECTION 14: Transport information

The product had been tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3 (see section 2)

**EmS No:** F-A , S-I

**Marine pollutant:** No

**Environmental hazards:** Not applicable.

**Special precautions for user:** Not applicable.

**Proper Shipping name:** Lithium ion batteries

**Hazard Class:** Class 9

**UN/ID Number:** UN3480

**Packaging Group:** II

**Maritime transport:**

# Safety Data Sheets (SDSs)

Ref. No.: RZUN012026-1255-DS3

Page 8 of 9 Pages

**Label for conveyance:** Class 9 Lithium Batteries or Sodium Ion Batteries hazard label

The goods are complied with the requirements of Packing Instruction P903 of IMDG CODE (Amdt. 42-24) (2024 Edition).

## SECTION 15: Regulatory information

### International Regulation:

GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS)

Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations

IATA Dangerous Goods Regulations (DGR)

INTERNATIONAL MARITIME DANGEROUS GOODS CODE (IMDG CODE)

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)

### EU Regulation:

Regulation (EU) 2020/878: Revised Requirements for EU Safety Data Sheets

EU regulation (EC) 1272/2008 on "Classification, Labeling and Packaging of Substances and Mixtures" (CLP)

Registration, Evaluation and Authorization of Chemicals (REACH)

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)

### US Regulation:

American National Standard for Hazardous Workplace Chemicals – Hazard Evaluation and Safety Data Sheet and Precautionary Labeling Preparation

US DOT, Code of Federal Regulations, Title 49, Transportation, PT. 100-185

## SECTION 16: Other information

This file is only effective to the batteries(IntelliHome-5kWh-OD) provided by commissioner Ginlong Energy Storage Co., Ltd. . The commissioner provides the composition information of batteries, and promises its integrity and accuracy. Users should read this file carefully, and use the batteries in correct method. CVC Testing Technology Co., Ltd. (CVC) doesn't assume responsibility for any damage or loss because of misuse of batteries.

---

## Important

1. The test report is invalid without the official seal of CVC.
2. Nobody is allowed to photocopy or partly photocopy this test report without written permission of CVC.
3. The test report is invalid without the signatures of Ratifier, Reviewer and Testing engineer.
4. The test report is invalid if altered.
5. Objections to the test report must be submitted to CVC within 15 days.
6. This report is valid for the samples provided by commissioner only.

*\*The test data and test results given in this test report should only be used for purposes of scientific research, teaching and internal quality control when the CMA symbol is not presented. \**

Address: No.3, Tiantai 1st Road, Kaitai Avenue, Science City, Guangzhou, Guangdong, China.

Tel: 020 32293888

FAX: 020 32293889

Post Code: 510663

E-mail: office@cvc.org.cn

<http://www.cvc.org.cn>